

REMARKS

The present preliminary amendment is submitted to correct minor typographical errors. No new matter has been added.

Applicant respectfully contends that the claims are in condition for allowance. Allowance of the claims is respectfully requested.

Please charge any shortages and credit any overcharges to our Deposit Account No. 02-2666.

Respectfully submitted,  
BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP

Dated: December 31, 2001 Maria McCormack Sobrino  
Maria McCormack Sobrino  
Registration No. 31,639

12400 Wilshire Boulevard  
Seventh Floor  
Los Angeles, CA 90025-1026  
(408) 720-8300

I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail with sufficient postage in an envelope addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231

on December 31, 2001

Date of Deposit

Maureen R. Pettibone

Name of Person Mailing Correspondence

Maureen R. Pettibone

Signature

12/31/01

Date

## VERSION WITH MARKINGS TO SHOW CHANGES MADE

### IN THE SPECIFICATION

Please replace the paragraph beginning on page 17, line 29 and ending on page 18, line 12 with the following paragraph:

A more detailed flow diagram of the processes utilized in one embodiment of the present invention is illustrated in **Figure 6a**. **Figure 6b** is a table presenting a number of the variables that will be referenced in the following discussion. Referring to **Figure 6a**, the input consists of focus 605, focal length 610, aspect ratio and aperture values 615, infinity setting 620, f-stop and circle of confusion 625. Utilizing the focus 605, focal length 610, the true focal length 630 is determined. The true focal length may subsequently be reflected as a number provided to a user holding a field device, such as a handheld device, or graphically presented to the user as will be shown below. To determine the true focal length, a computation or a look-up table may be used, block 635. In one embodiment, the calculation is as follows:

$$[TFL = FL^2 / (Focus - FL),] \quad TFL = FL + (FL^2 / Focus - FL)$$

where the TFL represents the true focal length, FL represents the focal length input and focus is the Focus value input.

Please replace the paragraph starting on page 18, line 13 with the following paragraph:

Using mathematical equations may be sufficient for some simple lenses. However, very complex lenses, lenses that are of special design, or even lenses that are out of alignment or unstable may require a measurement and mapping of basic lens properties from which look-up tables may be generated. This may occur, for example, when a particular type of lens and camera combination is required or some photography has been already shot with a particular type of lens in camera that was not in perfect condition. Furthermore, it is fairly common for the markings on a lens to be slightly off. For instance, the marks to indicate focus setting on a lens can be off by enough to cause an object to be out of focus if one were to only go on the lens markings and not look through the viewfinder. Even some lenses that are considered in "perfect" functioning

condition simply do not operate according to the normal optical equations. There are a number of lenses, particularly zoom lenses and those designed for microscopic or macroscopic whose design is fundamentally non-linear. In these cases, changing lens attributes such as focus or the focal length (on a zoom lens) have unpredictable results. Thus, some mechanism needs to exist to adjust the recorded values so the values correspond to the true optical properties of the lens. A look-up table, for example lookup table 637, provides a mechanism for incorporating those lens peculiarities into the invention's calculations to correct for these abnormalities.

Please replace the paragraph starting on page 20, line 1 with the following paragraph:

Thus, in one embodiment, the following computation is performed to determine the correct horizontal and vertical field of view.

$$[Vfov = 2*(atan(Ap/Ar)/2, FL)] \quad \underline{Vfov = 2*(atan((Ap/Ar)/2), TFL)}$$

$$[Hfov = 2*(atan(Ap/2, FL))] \quad \underline{Hfov = 2*(atan(Ap/2), TFL)}$$

Please replace the paragraph starting on page 20, line 15 with the following paragraph:

In one embodiment, the clips are positioned according to the following equation:


$$[Clip\ Pos = (TFL/2.54)/Ar] \quad \underline{Clip\ Pos = (TFL = 2.54/Ap)}$$

Where Clip Pos represents the reference clip position in feet from the camera position, TFL represents the true focal length, and [Ar represents the film gate aspect ratio] Ap represents the film gate aperture size.

Please replace the paragraph starting on page 21, line 1 with the following paragraph:

The focus 605 and true focal length are also used to determine three-dimensional markers, such as scale and position 650, with respect to displayed image and lens characteristics. The hyper focal distance 660 also is used. In one embodiment, the markers are placed in accordance with the following equation:

$$[Marker\ Pos = (TFL/2.54)/Ar] \quad \underline{Marker\ Pos = (TFL = 2.54/Ap)}$$



**FIG. 6a**